

## Professional welding inverter with multiple good properties.

Three phase portable IGBT welding inverter. Very smooth DC output, Arc force, Hot start, Electric shock prevention, Digital Ampere display, Current preset. Allow  $\pm 20\%$  power supply fluctuation and generator friendly. Perfect with overheating, over load, over current, over/lack voltage. Usable electrodes: Acid, Basic, Stainless steel, Cast iron and even Cellulosic !



### Properties

Welding current:

**20 - 300 Amp.**

Main power supply:

**400/440 V - 50/60Hz**

Duty cycle:

**35% - 300 Amp.**

No load voltage:

**75 V**

Welding electrode diameters

**1,6 - 5,0mm**

Rated input capacity:

**11.9 KVA**

Dimensions:

**450x250x290mm**

Weight:

**26 kg**

Sitz: Hamburg; Registergericht: Hamburg; HRB 131738; Geschäftsführung: Dennis Rebling, Jan Rebling  
USt-IdNr.: DE294522319; Steuernummer: 247/753/00626

Rebtec GmbH  
Hein-Sass-Stieg 4  
21129 Hamburg

Tel.: +49 40 22 867 41 - 0  
Fax: +49 40 22 867 41 - 99  
info@rebtec.de

Hypovereinsbank  
IBAN: DE21200300000015642934  
BIC: HYVEDEMM300

